

APPLICATIONS AND LINES



All presses are designed to run aluminum, SR-, DR-, tin and TFS plate, lamination optional. Square or scroll cut and sheet sizes up to 1000 x 1200 mm, clip out and scratch free operation, web 0.6mm (OF0.8 mm), high precision for printed products, highest flexibility for fast change over.

DRAWN CANS: (307 x 111)	NO.OUT	SPM	(TYPE) CPM	BACK END
CNC-E-PV15	1	150	130	trim press TP15/1, redraw and trim press RTPV15/1
CNC-AF-PV15	1	150	140	trim press TP15/1, redraw and trim press RTPV15/1
CNC-DF-P35	3	150	450	trim press TP15/1, redraw and texture press RTPV15/3
CNC-DF-P35	4	150	600	trim press TP35/4, redraw and trim press RTPV40/4
CNC-OF-PD50	5	150	750	DRMTPV 80/4 redraw and trim press

	CAPS & CLOSURES:	NO.OUT	SPM	(TYPE)CPM	BACK END
LUG CAPS	CNC- E -P15	2	200	320	RTCL15/2 (Lugging and PVC Lining)
	CNC-AF-P35	6	200	960	RTCL35/6 (Lugging and PVC Lining)
	CNC-DF-P35	6	250	1350	
	CNC-DF-P45S	8	240	1800	RTCL 45/8 (Lugging and PVC Lining)
	CNC-OF(G)-P125	10/82mm	220	2200	
PT CAPS	CNC-DF-P35	5	200	1000	PVC-FREE Lining
PP CAPS	CNC-OF-P35	5	200	1000	PVC-FREE Lining
	CNC-OF-P40	11	220	2400	PVC-FREE Lining
	TPE Liner	4	125	500	PVC-FREE Lining



	SANITARY ENDS: Beverage ends (70mm)	NO.OUT	SPM	(TYPE) EPM	BACK END
ENDS	CNC-E-P15	1	250	200	single curler, single head liner
	CNC-AF-P35	6	260	1150	double curler, double head liner
	CNC-DF-P35	6	260	1380	single curler, rotary liner
	CNC-AF-P40	7	200	1150	double curler, double head liner
	CNC-DF-P40	7	200	1300	single curler, rotary liner
	CNC-DF-P40S	7	260	1680	single curler, rotary liner
	CNC-OF(G)-P125	9/99mm	260	2340	double curler, double rotary liner
	CNC-OF(G)-P125	15/73mm	260	3900	double curler, double rotary liner
EZO ENDS	CNC-DF-P35	5-6	250	1200	EOE-P-80
	CNC-OF(G)-P125	11	250	2400	EOE-P-125

GENERAL LINE:	NO.OUT (mm)	BLANK SIZE (mm)	DRAW DEPTH	(TYPE)PRODUCTS
CNC-E-P15	1	200	25	lids, rings, ends
CNC-E-PV15	1	200	40	cans, curled lids, triple tight rings
CNC-AF-P15	1	200	25	lids, rings, ends
CNC-AF-PV15	1	200	40	cans, curled lids, triple tight rings
CNC-AF-P35	2	200	25	lids, rings, shallow drawn cans
CNC-AF-P40	1-2	400	30	slip covers, big curled lids, ends
CNC-AF-PV40	1-2	400	45	drawn cans, pail covers



**ALFONS HAAR
WORLDWIDE OFFICES**



**ALFONS HAAR
MASCHINENBAU GMBH & CO. KG**
Fangdieckstrasse 67 • D-22547 Hamburg
TEL +49 40 83391-0
FAX +49 40 844910
E-MAIL office@alfons-haar.de
INTERNET www.alfons-haar.de



ALFONS HAAR INC.
150 Advanced Drive • Springboro, OH 45066, U.S.A.
TEL +1 937 5602031 • FAX +1 937 5602032
E-MAIL alfons-haar@alfons-haar.us

ALFONS HAAR SINGAPORE
TEL +65 9833 2083 • FAX +65 63992646
E-MAIL alfonshaar.sg@gmail.com