PreciMA C490 PreciCONTROL BASED MEASURING UNIT



SAVE COSTS SAVE SPACE + WEIGHT

- 490 l/min wet hose 2"
- · Dry ventilation without wet return pipe

MID + ATEX approved





CountMASTER 4A Interactive interface between user and measuring unit


- Total safety against unintended measurement of air
- Completely mounted and configured ex works, ready to be installed and easily connected
- Full automatic control of all loading and discharge functions
- Long-term reliability of electronics due to robust, burn-in tested potting technology
- Contamination on product change limited to only 0.7 liters of residual volume inside PreciMA
- Easy electrical installation uses Field bus wiring system "PreciBUS". No wiring looms or terminal boxes
- Pneumatic logic elements and control blocks are no longer necessary




PreciMA C490

PreciCONTROL BASED MEASURING UNIT







TECHNICAL DATA

WFIGHT: 14,5 - 17,7 kg MEASUREMENT RANGE: 50 I/min - 500 I/min

MINIMUM MEASURING QUANTITY: 50 liters

MEASURING PRODUCT: Liquids, except water, with

a kinematic viscosity of <20mPas at 20°C, e.g. diesel, kerosene, heating oil, bio diesel.

MAX. OPERATION PRESSURE: 10bar

POWER SUPPLY: 24V V DC on-board electronic unit

(15....32V)

OPTIONS

The central controller, CountMASTER 4, can be extended by software upgrade:

- Product Return with Flow Check
- Wet hose delivery valve 2

(For more information see separate

brochures)